

DLB MONOFASE STANDARD

DLB1



**POWER MANAGEMENT DEVICE, SELF-POWERED,
COMPLIANT WITH SINGLE PHASE BIAN.CO EASY EV CHARGERS**

Technical information

Operating Temperature	-25 ÷ 55 °C
IP grade	IP20
Display	LCD
Rated frequency	50 - 60 Hz
Max. measurable current	100 A
Power supply	Self powered by EV Charger, via LAN
Ethernet cable standard length	5 m
Nr. of CT input ports	1
Fixing mode	DIN rail; Fixing bolts (flat surface needed)

Weight and Dimensions

Weight	100 g
Height	82 mm
Width	67 mm
Length	35 mm

Certifications, Patents and Approvals

UKCA Mark	Yes
CE Mark	Yes

Compatibility and Connections

Software included	Integrated into EV Charger
Software name	Android and iOS app ("BIAN.CO EASY APP")
LAN	Only for power supply and con- nection with EV Charger

Logistics

Customs code	85371091
Standard packaging (GTIN)	8051316087614
Storage temperature	-30 ÷ 70 °C
Packaging length	159 mm
Packaging width	157 mm
Packaging height	90 mm
Total weight	0,5 kg

Sales supply

Management Unit
DIN rail adapters
Guida DIN
Nr. 1 pre-cabled CTs
5m LAN cable
Product card

Compatible Products

EVC7.4S/1S
EVC7.4S/1C