

DLB MONOFASE PV INTEGRATED

DLB1-PV



**POWER MANAGEMENT DEVICE, SELF-POWERED,
COMPLIANT WITH SINGLE PHASE BIAN.CO EASY EV CHARGERS**

Technical information	
Operating Temperature	-25 ÷ 55 °C
IP grade	IP20
Display	OLED
Rated frequency	50 - 60 Hz
Max. measurable current	100 A
Power supply	Self powered by EV Charger, via LAN
Ethernet cable standard length	5 m
Nr. of CT input ports	2
Fixing mode	DIN rail; Fixing bolts (flat surface needed)

Weight and Dimensions	
Weight	100 g
Height	82 mm
Width	67 mm
Length	35 mm

Certifications, Patents and Approvals	
UKCA Mark	Yes
CE Mark	Yes

Compatibility and Connections	
Software included	Integrated into EV Charger
Software name	Android and iOS app ("BIAN.CO EASY APP")
LAN	Only for power supply and connection with EV Charger

Logistics	
Customs code	85371091
Standard packaging (GTIN)	8051316087614
Storage temperature	-30 ÷ 70 °C
Packaging length	159 mm
Packaging width	157 mm
Packaging height	90 mm
Total weight	0,5 kg

Sales supply	
Management Unit	
DIN rail adapters	
Guida DIN	
Nr. 2 pre-cabled CTs	
5m LAN cable	
Product card	

Compatible Products	
EVC7.4S/1S	
EVC7.4S/1C	